



## **L20/480 HYGIENIC GRP DOOR SETS**

### **Lami KMS Type Fire Rated Single Action Door Sets**

Manufacturer and supplier:

Lami Doors UK Ltd., Station House, Stamford New Road, Altrincham, Cheshire, WA14 1EP.

Tel. +44 (0)161 924 2217, Fax +44 (0)161 924 2218,

[lamidoors@lamidoors.com](mailto:lamidoors@lamidoors.com)

[www.lamidoors.com](http://www.lamidoors.com)

- Door leaf: Pressure moulded seamless Glass Reinforced Polyester 40mm thick door leaf. Fire resisting core material. Moisture absorption 0 %.
- Reference: **Lami Type F/KMS F30 or F60 or F120 or F240** fire rated single action door set.
- Sizes: [See list of manufacturer's standard sizes.](#)
- Leaf colour: [Selection from Lami standard colour range](#) or colour from RAL/BS colour charts.
- Frame: Pressure moulded GRP frame in widths of 95mm or 135mm with internal reinforcement, factory prepared mitred corner joints, fitted hinges and pre-drilled fixing points.
- Frame colour: [Selection from Lami standard colour range](#) or colour from RAL/BS colour charts.
- Hinges: Corrosion and acid proof Grade 316 stainless steel 'lift-off' hinges.
- Seals: EPDM cold smoke seal and flush fitted intumescent fire seal in the frame.
- Ironmongery: Selection from Lami standard stainless steel/aluminium c/w non hold open closer or client specified ironmongery. Optional for DDA and BS8300 compliance.
- Glazing: Triple glazed intermediate wired glass or clear Pyrodur panel with outer panels laminated safety glass, finished flush with both faces of door, standard size 200x500mm or other sizes on request. Optional for DDA and BS8300 compliance.
- Protection: 1mm thick Stainless Steel Grade 304 or 1mm thick Acid Proof Stainless Steel Grade 316 brushed finish or 5mm thick smooth polyethylene in standard grey colour RAL 7035, tape fixed to door leaf.
- Double leaf: Flush bolts Roca 849 in leading edge.  
Stainless steel centre rebate with rubber seal.