



## **L20/480    HYGIENIC GRP DOOR SETS**

### **Lami KAS Type Non Fire Rated Single Action Door Sets**

Manufacturer and supplier:

Lami Doors UK Ltd., Station House, Stamford New Road, Altrincham,  
Cheshire, WA14 1EP.

Tel. +44 (0)161 924 2217, Fax +44 (0)161 924 2218,

[lamidoors@lamidoors.com](mailto:lamidoors@lamidoors.com)

[www.lamidoors.com](http://www.lamidoors.com)

Door leaf: Pressure moulded seamless Glass Reinforced Polyester 40mm thick door leaf. HCFC free closed cell polyurethane core. Moisture absorption 0 %.

Reference: **Lami Type KAS** non fire rated single action door set

Sizes: [See list of manufacturer's standard sizes.](#)

Leaf colour: [Selection from Lami standard colour range](#) or colour from RAL/BS colour charts

Frame: Adjustable aluminium wrap around frame to suit wall thickness from 68-256mm, integral adjustable packers at fixing points to ease the installation. Integral white clip-on trim fully concealing the frame fixings.

Frame colour: Powder coated RAL9016 white or natural anodized aluminium.  
Optional for colour from RAL/BS charts

Hinges: Corrosion and acid proof Grade 316 stainless steel 'lift-off' hinges.

Seals: Integral silicon seal in the frame.

Ironmongery: Selection from Lami standard stainless steel/aluminium or client specified ironmongery. Optional for DDA and BS8300 compliance.

Glazing: Double glazed with laminate safety glass, finished flush with both faces of door, size to client specification. Optional for DDA and BS8300 compliance.

Protection: 5mm thick smooth polyethylene in standard grey colour RAL 7035 or 1mm thick Stainless Steel Grade 304 or 1mm thick Acid Proof Stainless Steel Grade 316 brushed finish, tape fixed to door leaf.

Double leaf: Flush bolts Roca 849 in leading edge.  
Stainless steel or aluminium centre rebate with rubber seal.