



L20/480 HYGIENIC GRP DOOR SETS

LAMI KLA Type Non Fire Rated Automatic Sliding Door Sets

Manufacturer and supplier:

Lami Doors UK Ltd., Station House, Stamford New Road, Altrincham, Cheshire, WA14 1EP.

Tel. +44 (0)161 924 2217, Fax +44 (0)161 924 2218,

lamidoors@lamidoors.com

www.lamidoors.com

- Door leaf: Pressure moulded seamless Glass Reinforced Polyester 40mm thick door leaf. HCFC free closed cell polyurethane core. Moisture absorption 0 %
- Reference: **LAMI Type KLA** non fire rated sliding door set
- Sizes: [See list of manufacturer's standard sizes](#)
- Leaf colour: [Selection from LAMI standard colour range](#) or colour from RAL/BS colour charts
- Frame: Adjustable aluminium wrap around frame to suit wall thickness of 68-256mm or pressure moulded GRP frame in width of 88mm or steel/stainless steel frame to suit wall thickness
- Frame colour: RAL 9016 white powder coated (metals), or GRP. Natural anodized aluminium or brushed stainless steel. Or options from RAL/BS colour charts
- Track system: Proprietary automatic system f.ex. Besam, Dorma, Abloy or Geze. C/w Lami aluminium bottom fitted guide with stainless steel floor guide and adjustable rubber slide stops
- Seals: Integral silicon seal or EPDM rubber seal in the frame
- Ironmongery: Selection from Lami standard stainless steel/aluminium or client specified ironmongery. Optional for DDA and BS8300 compliance
- Glazing: Double glazed with laminate safety glass finished flush with both faces of door, size to client specification. Optional for DDA and BS8300 compliance
- Protection: 5mm thick smooth polyethylene in standard grey colour RAL 7035 or 1mm thick Stainless Steel Grade 304 or 1mm thick Acid Proof Stainless Steel Grade 316, brushed finish, tape fixed to door leaf
- Optional: Door set c/w radiation protection up to 4mm